



FogBl

FogBI is an easily worked mortar which can be used for grouting prefabricated storey partitions. Particularly effective in narrow joints.

Fills out even narrow joints

FogBI is a pumpable easily worked cement mortar designed for situations requiring flexible casting of reliable joints. Our most popular liquid mortar is self-compacting FogBI, which fills out your joints with minimal effort and no need for external vibration. FogBI is supplied ready-mixed to your site, so you can dispense with precursor storage and mixing equipment on site. This frees up valuable time and space.

Documented quality

As we produce FogBI in our own concrete plants, you can be certain that the mortar will always have a controlled, uniform quality. Properties such as consistency and strength class are controlled by the manufacturer and documented.

- Areas of application
- FogBI is primarily used for grouting joints .

Handling tips

With its special composition, FogBI can be pumped in 1½" hoses. Otherwise FogBI must be handled as ordinary concrete. For instance, it must be protected from drying out and early freezing.

- Technical summary
- Ready-mixed joint grout with maximum aggregate size of 8 mm for reliable grouting
- Normally produced with Bascement or Byggcement but can also be supplied with Anläggningscement
- Fulfils Swedish Standards SS-EN 206 and SS137003
- The following grades are available as standard:

Strength class	Slump class	Max. W/C _{equiv.}
FogBI C28/35	S3 – S5, SKB SF1 – SF2	0.60
FogBI C32/40	S3 – S5, SKB SF1 – SF2	0.55
FogBI C40/50	S3 – S5, SKB SF1 – SF2	0.45
FogBI C45/55	S3 – S5, SKB SF1 – SF2	0,40